

- SLASHERS ARE SUPPLIED STANDARD WITH THE FOLLOWING:**
1. PTO shaft and torque limiting slip clutch
 2. Category 2 Hitch pins
 3. Front apron and rear hinged protection guard as well as PTO slip clutch cover
 4. All slashers have an adjustable skid height to provide the required finish
 5. The Maxi-Cut 1800 models have adjustable three point hitches that can be adjusted left and right to work in difficult conditions, e.g. under trees and bushes

- SWAILEMSNER WORD STANDAARD VOORSIEN VAN DIE VOLGENDE:**
1. Attakas en glykoppelaar
 2. Kategorie 2 hakpenne
 3. Beskerminingsplate voor en agter asook oor die glykoppelaar
 4. Alle swailemsnysers het verstelbare glyplate om die verlangde sny hoogte te verseker
 5. Die Maxi-Cut 1800 modelle het verstelbare hakpunte wat links en regs kan skuif om in moeilike areas te sny, byvoorbeeld onder bome & bosse

NOTAS / NOTES

MODELLE / MODELS		Ratkas (kW) / Gearbox (kW)	Olie / Oil	Trekker kW / Tractor kW	Attakas / PTO Shaft	Glykoppelaar / Slip Clutch	Sny Wydte (mm) / Cutting Width (mm)	Sny Hoogte (mm) / Cutting Height (mm)	Aantal Lemme / Number of Blades	Glyplaat hoogte (mm) / Skid Height (mm)	Masjien Wydte (mm) / Machine Width (mm)	Masjien Lengte (mm) / Machine Length (mm)	Totale gewig (kg) / Total mass (kg)
1.8 m	80	85W140	55 - 90 kW	A 6	FF2 (STD)	1840	20 - 180	4 (STD)	330	1810	2130	2140	660
1.5 m	80	85W140	45 - 70 kW	A 6	FF2 (STD)	1640	20 - 180	4 (STD)	330	1810	1920	1920	590

SPEKIFIKASIES / SPECIFICATIONS

**STANDAARD WENTELSNYERS
STANDAARD SLASHERS**



TWK LANDBOU BPK
POSBUS 128
PIET RETIEF, 2380
TEL: 017 824 1000
 e-mail: engineering@twkagri.com

