



TWK LANDBOU BPK

POSBUS 128

PIET RETIEF, 2380

TEL: 017 824 1000

e-mail: engineering@twkagri.com

MAXI-DISC

TRAILED TYPE DISC HARROWS

SLEEPTIPE KONTRASNY EGGE

SPECIFICATIONS

- Hi-tensile tubular frame and gang beams
- 4" x 10" Hydraulic cylinders
MK I: 1 per Implement
MK II: 2 per Implement
- Trailed type disc harrow
- Heavy duty bearings (Oil or Grease)
- Tyres: 11L x 16 (12 ply)
MK I: 2 wheels per implement
MK II: 4 wheels per implement
- Disc Blade size: 710 mm x 8 mm (28") cutaway discs
- Disc spacing: 275 mm (10.5")
- kW required: ± 3.6 - 4.0 kW per disc blade
- Weight per disc blade: ± 118 - 120 kg
- Width of cut:

MK I

Maxi-Disc 2100/18 - 2,17
Maxi-Disc 2400/20 - 2,42 m
Maxi-Disc 3000/24 - 3,08 m
Maxi-Disc 3600/28 - 3,67 m

MK II

Maxi-Disc 3600/28 - 3,67 m
Maxi-Disc 4200/32 - 4,27 m
Maxi-Disc 4800/36 - 4,88 m
Maxi-Disc 5400/40 - 5,49 m
Maxi-Disc 6000/44 - 6,08 m
Maxi-Disc 6600/48 - 6,69 m

- Adjustable scrapers
- Number of disc blades:

MK I

Maxi-Disc 2100/18 - 18
Maxi-Disc 2400/20 - 20
Maxi-Disc 3000/24 - 24
Maxi-Disc 3600/28 - 28

MK II

Maxi-Disc 3600/28 - 28
Maxi-Disc 4200/32 - 32
Maxi-Disc 4800/36 - 36
Maxi-Disc 5400/40 - 40
Maxi-Disc 6000/44 - 44
Maxi-Disc 6600/48 - 48

SPESIFIKASIES

- Hoogs rekbare buisvormige staalraam & balke
- 4" x 10" Hidrouliese silinders
MK I: 1 per Implement
MK II: 2 per Implement
- Sleptipe kontrasny-eg
- Swaardiens laers (Olie of Ghries)
- Bande: 11L x 16 (12 laag)
MK I: 2 wiele per implement
MK II: 4 wiele per implement
- Skottelgrootte: 710 mm x 8 mm (28") gehapte skottels
- Skottelspasiëring: 275 mm (10.5")
- kW benodig: ± 3.6 - 4.0 kW per skottel
- Gewig per skottel: ± 118 - 120 kg
- Snywydtes:

MK I

Maxi-Disc 2100/18 - 2,17 m
Maxi-Disc 2400/20 - 2,42 m
Maxi-Disc 3000/24 - 3,08 m
Maxi-Disc 3600/28 - 3,67 m

MK II

Maxi-Disc 3600/28 - 3,67 m
Maxi-Disc 4200/32 - 4,27 m
Maxi-Disc 4800/36 - 4,88 m
Maxi-Disc 5400/40 - 5,49 m
Maxi-Disc 6000/44 - 6,08 m
Maxi-Disc 6600/48 - 6,69 m

- Verstelbare skrapers
- Aantal Skottels:

MK I

Maxi-Disc 2100/18 - 18
Maxi-Disc 2400/20 - 20
Maxi-Disc 3000/24 - 24
Maxi-Disc 3600/28 - 28

MK II

Maxi-Disc 3600/28 - 28
Maxi-Disc 4200/32 - 32
Maxi-Disc 4800/36 - 36
Maxi-Disc 5400/40 - 40
Maxi-Disc 6000/44 - 44
Maxi-Disc 6600/48 - 48