



TWK LANDBOU BPK
POSBUS 128
PIET RETIEF, 2380
TEL: 017 824 1000
e-mail: engineering@twkagri.com

MAXI-DISC

Maxi-Disc	16/1800	L
Maxi-Disc	18/2100	L
Maxi-Disc	20/2300	L
Maxi-Disc	22/2500	L
Maxi-Disc	24/2700	L

SPECIFICATIONS

- Hi-tensile tubular frame (100 x 6 sq tubing)
- Weight per disc blade: 65 kg
- Disc blade size: 610 mm (24")
- Cat II hitch
- Bearings: Re-greasable sealed bearing
- kW required: 2.5 kW per disc blade
- 45 mm Solid Gang Axles
- Width of cut: 1,8 m - 2,7 m
- Disc spacing: 235 mm
- Adjustable gang beams

SPESIFIKASIES

- Hoogs rekbare buisvormige staalraam (100 x 6 vierkant staal)
- Gewig per skottel: 65 kg
- Skottelgrootte: 610 mm (24")
- Kat II hakpunte
- Laers: Ghriesbare verseelbare rollaers
- kW benodig: 2.5 kW per skottel
- 45 mm Skottel Aste
- Snywydte: 1,8 m - 2,7 m
- Skottelspasiëring: 235 mm
- Verstelbare gange