



TWK LANDBOU BPK
POSBUS 128
PIET RETIEF, 2380
TEL: 017 824 1000
e-mail: engineering@twkagri.com

MAXI-RIDGE

Maxi-Ridge 1 **Maxi-Ridge 3**

SPECIFICATIONS

- High-tensile tubular frame (150 x 100 Rect Tubing)
- Disc blade size: 660 mm (26")
- Cat II linkage
- Bearings: Re-greasable sealed ball bearings
- Width setting: 0 - 1.8 m
- Ridger Unit adjustments -
Horizontal: 15° - 30° - 45°
Vertical: 10° - 20° - 30°
- Available in single row or three rows

Optional Extras

1. Marker Arms (Hydraulic)
2. Gauge Wheels (11 L x 16)

SPESIFIKASIES

- Hoogs rekbare buisvormige staalraam (150 x 100 Reghoek Staal)
- Skottelgrootte: 660 mm (26")
- Kat II hakpunte
- Laers: Ghriesbare verseelbare rollaers
- Wydte verstelling: 0 - 1.8 m
- Operter eenheid verstellings -
Horisontaal: 15° - 30° - 45°
Vertikaal: 10° - 20° - 30°
- Beskikbaar in enkelry of drie rye

Opsionele Ekstras

1. Merker Arms (Hidroulies)
2. Dieptebeheerwiele (11 L x 16)